

Boiler and pressure vessel steel

**Metinvest Trameal
Ferriera Valsider
Spartan UK**

EN10028-2

Cert. 3.1 - 3.2 - PED – ADW1	Thickness (mm)	Width (mm)¹	Weight (tons)²	Delivery condition
P235GH	4-120	3150 max	3,0-15,0	NR - NF
P265GH	4-120	3150 max	3,0-15,0	NR - NF
P295GH	4-120	3150 max	3,0-15,0	NR - NF
P355GH	4-120	3150 max	3,0-15,0	NR - NF
16Mo3	6-100	3150 max	3,0-15,0	NR - NF
13CrMo4-5	8-80	3150 max	3,0-15,0	NF

EN10028-3

Cert. 3.1 - 3.2 - PED - ADW1

P275NH	4-120	3150 max	3,0-15,0	NR - NF
P275NL1	4-120	3150 max	3,0-15,0	NF
P275NL2	4-120	3150 max	3,0-15,0	NF
P355N	4-120	3150 max	3,0-15,0	NR - NF
P355NH	4-120	3150 max	3,0-15,0	NR - NF
P355NL1	4-120	3150 max	3,0-15,0	NF
P355NL2	4-120	3150 max	3,0-15,0	NF
P460NH	8-120	3150 max	3,0-15,0	NF
P460NL1	8-100	3150 max	3,0-15,0	NF
P460NL2	8-100	3150 max	3,0-15,0	NF

EN10028-4

Cert. 3.1 - 3.2 - 3.2 R.I.NA.

13 MnNi 6-3 ³	8-40	3150 max	3,0-15,0	NF
12 Ni 14	8-50	3150 max	3,0-15,0	NF

NF A36-215

Cert. 3.1 - 3.2 - PED

P440NJ4	8-12	3150 max	3,0-15,0	NF
P460NJ2	8-12	3150 max	3,0-15,0	NF

¹ Width min/max related to thickness and heat treatment

² Minimum and maximum tonnage related to thickness and slabs availability

³ Certified by R.I.NA. Shipping Register as 510LF for thickness 8-35mm

- NR Normalizing rolling
- NF Normalized in furnace

All grades can be supplied with improved properties on thickness direction